

Component - Plastics

E121562

SABIC INNOVATIVE PLASTICS US L L C

AMERICAS - RESIN, 1 PLASTICS AVE, PITTSFIELD MA 01201

FR6, FR60 (GG), FR63 (GG), FR65 (GG), FR6+, FR700(GG), FR7+, FR8+, FR25A

Polycarbonate (PC), "Lexan", furnished as films and sheets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Elong	RTI Str
CL	0.051	VTM-0	-	-	80	80	80
CL, BK	0.13	VTM-0	-	-	80	80	80
ALL	0.23	V-0	1	0	130	125	130
	0.38	V-0	0	0	130	125	130
	0.51	V-0	0	0	130	125	130
	3.0	V-0	-	-	130	125	130

Comparative Tracking Index (CTI): **3**

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate
(HVTR): **4**

High Volt, Low Current Arc Resis (D495): -

Dielectric Strength (kV/mm): **66**Volume Resistivity (10^x ohm-cm) : -**(GG) - Denotes a global grade formulation previously in File E161759.****+ - May be followed by the letter R.****NOTE - Material designation may be followed by a color nomenclature consisting of either an alpha/numeric or numeric/alpha combination.**

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1983-01-11

Last Revised: 2009-06-25

Underwriters Laboratories Inc®

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness	
			Tested (mm)	Value
Flammability	ISO 9773, IEC 60695-11-10	Class (color)	0.051	VTM-0 (CL)
			0.13	VTM-0 (CL, BK)
			0.23	V-0 (ALL)
			0.38	V-0 (ALL)
			0.51	V-0 (ALL)
			3.0	V-0 (ALL)
Glow-Wire Flammability (GWF1)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-

Underwriters Laboratories Inc®